


FumeSafe[™]

3. Pre-filter 4. Main filter What to specify...

3-15 Tip Fume Extraction Unit Voltage 230V ±10% or 120V ±10% **Auto Sensing** Vacuum Control 072200 **Dual Voltage** 0.45 kW Wattage **Blower Works** Frequency 50Hz / 60 Hz Anywhere in Cabinet height 493 mm the World! Cabinet width (not inc hose) 471 mm Cabinet depth (not inc hose) 430 mm 26 Kg Cabinet weight (inc filters) Construction Stainless Steel Construction Precision engineered brushed stainless steel units. High performance continuous run brushless motors. Quick and simple to relocate.














Supplied with 3 universal iron kits - 300001

Controls

Visual and Audible Filter Blocked Warning

Alerts the operator when a filter starts to block so that a replacement filter can be acquired and downtime can be avoided.

Controls & System Features...

- Speed Control
- Dual voltage brushless blower
- Low capital and running costs
- · Quick change pre-filters deliver longer filter life
- Submicronic (HEPA) filtration removes 99.997% of particles down to 0.3 microns
- Activated carbon filtration removes harmful gas
- Simple to install and quiet in operation
- Easy to relocate
- Precision made from stainless steel
- Filter blocked alarm and LED

Includes:

- I x Main filter
- I x Pre-filter pad
- Lx Exhaust filter
- I x Power cable
- I x Connection kit
- I x Pipework kit
- 3 x Universal iron kits

Accessories

Please see the accessories section at the back of this brochure.